

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : HI-LITE TINT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Embalming Cosmetic Dye

Use of the substance/mixture : For professional use only

1.3. Details of the supplier of the safety data sheet

THE CHAMPION COMPANY
400 Harrison Street
Springfield, Ohio 45505

Telephone No. (937) 324-5681

1.4. Emergency telephone number

INFOTRAC: 1-800-535-5053 DOMESTIC or 352-323-3500 INTERNATIONAL

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 2	H225
Acute Tox. 3 (Oral)	H301
Acute Tox. 3 (Dermal)	H311
Acute Tox. 3 (Inhalation:vapor)	H331
STOT SE 1	H370

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS02



GHS06



GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H225 - Highly flammable liquid and vapor
H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled
H370 - Causes damage to organs (Optic nerve and central nervous system)Precautionary statements (GHS-US) : P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking
P233 - Keep container tightly closed
P240 - Ground container and receiving equipment
P241 - Use explosion-proof electrical, ventilating, lighting, and equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P260 - Do not breathe dust, fume, mist, spray, vapors
P261 - Avoid breathing dust, fume, mist, spray, vapors
P264 - Wash hands and other skin exposed area thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P271 - Use only in a well-ventilated area
P280 - Wear protective clothing, protective gloves, eye protection, face protection
P285 - In case of inadequate ventilation wear respiratory protection
P301+P310 - If swallowed: Immediately call a POISON CENTER
P302+P352 - If on skin: Wash with plenty of water
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P307+P311 - If exposed: Call a doctor
P311 - Call a POISON CENTER
P312 - Call a POISON CENTER
P330 - Rinse mouth

HI-LITE TINT

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

P361 - Take off immediately all contaminated clothing
P363 - Wash contaminated clothing before reuse
P370+P378 - In case of fire: Use alcohol resistant foam, dry powder, carbon dioxide (CO2) to extinguish
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents and container to comply with applicable local, state, national and international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Methyl alcohol	(CAS No) 67-56-1	95 - 98	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapor), H331 STOT SE 1, H370

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. Call a POISON CENTER.
First-aid measures after inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. by trained personnel. Immediately call a doctor.
First-aid measures after skin contact : Rinse skin with water. Wash with plenty of soap and water. Take off immediately all contaminated clothing. Immediately call a doctor.
First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for at least 15 minutes. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion : Rinse mouth thoroughly with water. Do NOT induce vomiting. Obtain emergency medical attention. Immediately call a POISON CENTER.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Methanol in high concentration may cause blindness and effects on the central nervous system. optic nerve. Death in extreme cases. Repeated or prolonged exposure to high levels may affect the liver and kidneys.
Symptoms/injuries after inhalation : Toxic if inhaled. Danger of serious damage to health by prolonged exposure through inhalation.
Symptoms/injuries after skin contact : Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin.
Symptoms/injuries after eye contact : Irritating to eyes.
Symptoms/injuries after ingestion : Toxic if swallowed. The swallowing of even a small amount of methanol can cause blindness or lead to death. The following may result in the case of a low dosage: nausea, headache, stomach-ache, vomiting and impaired vision (blurred vision, photophobia). There is furthermore risk of damage to liver, kidneys and heart. Effects may be delayed and manifest within 18 to 48 hours. Stinging sensation. Headache. Disorientation. Dizziness. Unconsciousness. Contains Methanol; constant ingestion of Methanol can lead to cirrhosis of the liver.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Alcohol resistant foam. Dry powder. Carbon dioxide. Water spray or fog.
Unsuitable extinguishing media : Do not use a heavy water stream.

HI-LITE TINT

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapor.
- Explosion hazard : May form flammable/explosive vapor-air mixture.
- Reactivity : May form flammable/explosive vapor-air mixture.

5.3. Advice for firefighters

- Firefighting instructions : Evacuate area and fight fire from a safe distance. Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering environment.
- Protective equipment for firefighters : Do not enter fire area without proper protective equipment, including respiratory protection. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
- Other information : Vapors can travel considerable distances to a source of ignition where they can ignite, flash back, or explode. On combustion, forms: carbon oxides (CO and CO₂). Formaldehyde. Alcohols burn with a pale blue flame which may be extremely hard to see under normal lighting conditions. Personnel may be able to feel the heat of the fire without seeing flames. Extreme caution must be exercised in fighting alcohol fires.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Ensure adequate ventilation. Stop leak if safe to do so. Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking. Special attention should be given to low areas/pits where flammable vapors can accumulate.

6.1.1. For non-emergency personnel

- Protective equipment : Wear suitable protective clothing, gloves and eye/face protection. For further information refer to section 8 : Exposure-controls/personal protection.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Evacuate unnecessary personnel. Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Dispose in a safe manner in accordance with local, state, national and international regulations.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.
- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No naked lights. No smoking. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Avoid breathing vapors, mist and spray.
- Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands and other exposed skin area thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment.
- Storage conditions : Keep out of reach of children. Keep only in the original container in a cool well ventilated place. Keep in fireproof place. Keep container tightly closed. Keep container dry. Keep away from heat and direct sunlight. Keep away from ignition sources (including static discharges). keep away from incompatible materials.
- Incompatible materials : Strong acids, bases. Strong oxidizing agents.

HI-LITE TINT

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

- Storage area : Storage area must meet OSHA requirements and applicable fire codes. Smoking, eating and drinking should be prohibited in areas of storage and use. Ensure adequate ventilation of the storage area.
- Special rules on packaging : Correctly labelled. Do not store in unlabeled containers.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Methyl alcohol (67-56-1)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	260 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm

8.2. Exposure controls

- Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Control airborne concentrations below the exposure limits. Ensure adequate ventilation. Use electrical equipment that conforms to national electric code. Use explosion-proof equipment.
- Personal protective equipment : Avoid all unnecessary exposure. Wear protective clothing, protective gloves, eye protection/goggles, face protection. For certain operations, additional Personal Protection Equipment (PPE) may be required.
- Hand protection : Wear impermeable protective nitrile gloves. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.
- Eye protection : Contact lenses should not be worn. Chemical goggles and face shields are required to prevent potential eye contact, irritation or injury.
- Skin and body protection : Long sleeved protective clothing. Overall. Rubber apron, boots, safety foot-wear.
- Respiratory protection : In case of insufficient ventilation. Wear suitable respiratory equipment. Approved organic vapor respirator.
- Environmental exposure controls : Avoid discharge to the environment. Prevent entry to sewers and public waters.
- Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Clear
- Color : Light red
- Odor : Slight alcohol-like
- Odor threshold : No data available
- pH : No data available
- Relative evaporation rate (butyl acetate=1) : > 1
- Melting point : No data available
- Freezing point : No data available
- Boiling point : 64.5 °C (148 °F)
- Flash point : 11 °C (52 °F) (closed up)
- Auto-ignition temperature : No data available
- Decomposition temperature : No data available
- Flammability (solid, gas) : No data available
- Vapor pressure : No data available
- Relative vapor density at 20 °C : No data available
- Relative density : No data available
- Density : 0.79 g/cm³ Specific Gravity
- Solubility : Water: completely miscible
- Log Pow : No data available

HI-LITE TINT

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 6.7 – 36 vol%

9.2. Other information

VOC content	: Percent volatiles 95
-------------	------------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

May form flammable/explosive vapor-air mixture.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

10.6. Hazardous decomposition products

Fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Toxic if swallowed. Toxic in contact with skin. Toxic if inhaled.

HI-LITE TINT	
ATE US (oral)	100.00000000 mg/kg bodyweight
ATE US (dermal)	300.00000000 mg/kg bodyweight
ATE US (vapors)	3.00000000 mg/l/4h

Methyl alcohol (67-56-1)	
LC50 inhalation rat (mg/l)	130.7 mg/l/4h (lit. ECHA)
ATE US (oral)	100.00000000 mg/kg bodyweight
ATE US (dermal)	300.00000000 mg/kg bodyweight
ATE US (vapors)	3.00000000 mg/l/4h

Skin corrosion/irritation	: Not classified Based on available data, the classification criteria are not met.
Serious eye damage/irritation	: Not classified Based on available data, the classification criteria are not met.
Respiratory or skin sensitisation	: Not classified Based on available data, the classification criteria are not met.
Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met.
Carcinogenicity	: Not classified Based on available data, the classification criteria are not met.
Reproductive toxicity	: Not classified Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure)	: Causes damage to organs.
Specific target organ toxicity (repeated exposure)	: Not classified Based on available data, the classification criteria are not met.

HI-LITE TINT

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Aspiration hazard	: Not classified Based on available data, the classification criteria are not met.
Potential Adverse human health effects and symptoms	: Toxic if swallowed. Toxic in contact with skin. Toxic if inhaled.
Symptoms/injuries after inhalation	: Toxic if inhaled. Danger of serious damage to health by prolonged exposure through inhalation.
Symptoms/injuries after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin.
Symptoms/injuries after eye contact	: Irritating to eyes.
Symptoms/injuries after ingestion	: Toxic if swallowed. The swallowing of even a small amount of methanol can cause blindness or lead to death. The following may result in the case of a low dosage: nausea, headache, stomach-ache, vomiting and impaired vision (blurred vision, photophobia). There is furthermore risk of damage to liver, kidneys and heart. Effects may be delayed and manifest within 18 to 48 hours. Stinging sensation. Headache. Disorientation. Dizziness. Unconsciousness. Contains ethanol; constant ingestion of ethanol can lead to cirrhosis of the liver.

SECTION 12: Ecological information

12.1. Toxicity

Methyl alcohol (67-56-1)	
LC50 fishes 1	> 12700 mg/l 96 hours
EC50 Daphnia 1	> 10000 mg/l

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer	: No additional information available
Effect on the global warming	: No additional information available
Other information	: Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations	: It is the responsibility of the user to determine if disposal material is hazardous according to federal, state and local regulations. Dispose in a safe manner in accordance with local, state, national and international regulations.
Additional information	: Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials	: Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14: Transport information

In accordance with DOT	
Transport document description	: UN1230, Methanol, 3, PGII, Ltd. qty.
Hazard labels (DOT)	: 3 - Flammable liquid



Packing group (DOT)	: II - Medium Danger
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 1 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L

HI-LITE TINT

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"

Additional information

Other information : No supplementary information available.

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

HI-LITE TINT	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	5202 lb
SARA Section 313 - Emission Reporting	1.0 %

Methyl alcohol (67-56-1)	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	5000 lb
SARA Section 313 - Emission Reporting	1.0 %

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

No additional information available

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

No additional information available

15.2.2. National regulations

No additional information available

15.3. US State regulations

HI-LITE TINT()	
U.S. - California - Proposition 65 - Developmental Toxicity	Yes

Methyl alcohol (67-56-1)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
	Yes			

SECTION 16: Other information

Other information : None.

Full text of H-phrases: see section 16:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation:vapor)	Acute toxicity (inhalation:vapor) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Flam. Liq. 2	Flammable liquids Category 2

HI-LITE TINT

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

STOT SE 1	Specific target organ toxicity (single exposure) Category 1
H225	Highly flammable liquid and vapor
H301	Toxic if swallowed
H311	Toxic in contact with skin
H331	Toxic if inhaled
H370	Causes damage to organs

HMIS III Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible
Flammability : 3 Serious Hazard
Physical : 0 Minimal Hazard

SDS US (GHS HazCom 2012)

The information herein given is in good faith but no warranty, expressed or implied, is made, except that to the best of the Company's knowledge it is accurate. The Champion Company does not assume any legal responsibilities for use or dependence upon same. Customers may wish to conduct tests of their own. The user is urged to read the information provided on the label before using product.