



## JAUNDEXTONE CPF=8<sup>A</sup>

### Special Purpose Arterial Fluid with Entrone and AD-P

JAUNDEXTONE is a formaldehyde arterial fluid specifically for use in jaundice cases. It contains Entrone for achieving penetration to the point of complete saturation and AD-P for control of formaldehyde action to obtain better diffusion and improvement of cosmetic effect. JAUNDEXTONE is mild in action and highly penetrating with maximum distribution to tissues. JAUNDEXTONE will successfully embalm jaundice bodies without adverse effects. JAUNDEXTONE is not recommended as a general purpose arterial fluid. For best results, inject 3-4 gallons of solution.

PH-A <sup>1</sup>	DI-SAN <sup>2</sup>	JAUNDEXTONE MODERATE <sup>3</sup> FIRMNESS	HUMITONE <sup>4</sup>	DI-SAN <sup>5</sup> ADD FOR EXTRA FIRMNESS	HUMITONE <sup>6</sup> ADD TO RESTORE MOISTURE CONTENT
<b>3-4</b>	<b>1-2</b>	<b>16</b>	<b>1-2</b>	<b>1-2</b>	<b>4-8</b>
→ → <b>MIX IN THIS ORDER</b> → → <b>OUNCES PER GALLON</b>					

#### Notes:

- A - A value assigned to all Champion fluids ranking them on the basis of preservative ability using recommended dilutions in normal cases. The Champion Preservative Factor is not index but can equal it in certain fluids. It is derived from the total chemical composition of each fluid and results of extensive field research. The Champion Preservative Factor can be used by the embalmer to predict the reactivity, preservative value and firming action of Champion fluids.
- 1 - For proper water conditioning and pH balance to maximize fluid efficiency (if using soft water - reduce amount to 2-3 ozs.)
  - 2 - For sanitizing action in solution and improved fluid action in all non-glutaraldehyde based fluids.
  - 3 - Use Champion Coloro Dyes at 1 oz. / gallon or greater for maximum cosmetic effect. Abnormal cases with higher aldehyde demand (cancer, wasting diseases, etc.) may require additional fluid to insure preservation. Embalmer must adjust quantity used according to severity of case.
  - 4 - HUMECTANT to control aldehyde action and prevent dehydration during embalming. Use in all non-lanolin based fluids. Do not use in cases of moisture retention (edema, etc.).
  - 5 - For increased aldehyde action of fluid with improved rigidity and preservation. (Increases preservative factor of fluid without inducing dehydration or other unwanted effects.)
  - 6 - For maximum rehydration of tissues. Restores moisture in cases of dehydration or emaciation. Use in last 1 to 1-1/2 gallons of solution with intermittent or restricted drainage.

**BEFORE USING, READ SAFETY DATA SHEET.  
FOR PROFESSIONAL EMBALMING USE ONLY.**

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Trade name : JAUNDEXTONE

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Use of the substance/mixture : Arterial Embalming Fluid

Use of the substance/mixture : For professional use only

**1.3. Details of the supplier of the safety data sheet**THE CHAMPION COMPANY  
400 Harrison Street  
Springfield, Ohio 45505

Telephone No. (937) 324-5681

**1.4. Emergency telephone number**

INFOTRAC: 1-800-535-5053 DOMESTIC or 352-323-3500 INTERNATIONAL

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GHS-US classification**

Flam. Liq. 4	H227
Acute Tox. 4 (Oral)	H302
Acute Tox. 4 (Dermal)	H312
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Skin Sens. 1	H317
Carc. 1A	H350
STOT SE 2	H371

**2.2. Label elements****GHS-US labelling**

Hazard pictograms (GHS-US) :



GHS07

GHS08

Signal word (GHS-US) :

: Danger

Hazard statements (GHS-US) :

: H227 - Combustible liquid  
H302+H312 - Harmful if swallowed or in contact with skin  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation  
H350 - May cause cancer  
H371 - May cause damage to organs

Precautionary statements (GHS-US) :

: P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking  
P260 - Do not breathe dust, fume, mist, spray, vapors  
P261 - Avoid breathing dust, fume, mist, spray, vapors  
P264 - Wash hands thoroughly after handling  
P270 - Do not eat, drink or smoke when using this product  
P272 - Contaminated work clothing must not be allowed out of the workplace  
P280 - Wear protective clothing, protective gloves, eye protection, face protection  
P301+P312 - If swallowed: Call a POISON CENTER  
P302+P352 - If on skin: Wash with plenty of water  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P308+P313 - If exposed or concerned: Get medical attention  
P312 - Call a POISON CENTER

# JAUNDEXTONE

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

P330 - Rinse mouth  
P332+P313 - If skin irritation occurs: Get medical attention  
P333+P313 - If skin irritation or rash occurs: Get medical attention  
P337+P313 - If eye irritation persists: get medical attention  
P362 - Take off contaminated clothing and wash before reuse  
P370+P378 - In case of fire: Use alcohol resistant foam, dry powder, carbon dioxide (CO<sub>2</sub>) to extinguish  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents and container to comply with applicable local, state, national and international regulation.

### 2.3. Other hazards

other hazards which do not result in classification : Spilled material may present a slipping hazard.

### 2.4. Unknown acute toxicity (GHS-US)

No data available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Methyl alcohol	(CAS No) 67-56-1	5 - 8	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapor), H331 STOT SE 1, H370
Formaldehyde	(CAS No) 50-00-0	< 8	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 1A, H350 STOT SE 3, H335
Boric acid, disodium salt, pentahydrate	(CAS No) 12179-04-3	<1.5	Repr. 1B, H360
Boric acid (H <sub>3</sub> BO <sub>3</sub> )	(CAS No) 10043-35-3	<1	Repr. 1B, H360

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Call a doctor.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Keep victim warm and rested. Seek medical attention immediately. If breathing stops, give artificial respiration. Transfer to hospital rapidly. Immediately call a doctor.

First-aid measures after skin contact : Wash immediately with lots of water (15 minutes)/shower. Take off immediately all contaminated clothing. Get medical attention. Wash contaminated clothing before reuse.

First-aid measures after eye contact : In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. Seek medical attention immediately. Transport to hospital.

First-aid measures after ingestion : If swallowed, rinse mouth with water (only if the person is conscious). Immediately call a POISON CENTER. Give water or milk if the person is fully conscious. Seek medical advice (show the label where possible).

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : May cause damage to organs.

Symptoms/injuries after inhalation : May cause respiratory irritation. Danger of serious damage to health by prolonged exposure through inhalation. May cause cancer by inhalation. Difficulty in breathing. Causes damage to liver through prolonged or repeated exposure if inhaled. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination. Death in extreme cases.

# JAUNDEXTONE

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

- |                                      |   |
|--------------------------------------|---|
| Symptoms/injuries after skin contact | : Harmful in contact with skin. May cause an allergic skin reaction. Causes skin irritation. Absorbed through the skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard. Contains formaldehyde which can combine with epidermal protein to produce a hapten-protein couple capable of sensitising T-lymphocytes. Subsequent exposures cause a type IV hypersensitivity reaction. |
| Symptoms/injuries after eye contact  | : Causes serious eye irritation. Redness and pain. Impaired vision, watering of eyes, defects in the cornea. Burning sensation. Inflammation. Can cause blindness.  |
| Symptoms/injuries after ingestion    | : Harmful if swallowed. Swallowing a small quantity of this material will result in serious health hazard. This material contains methanol, which, when ingested, has cards acidosis, ocular toxicity ranging from diminished visual capacity to complete blindness, and death. Ingestion may cause nausea, vomiting and diarrhea. Swallowing can cause severe injury leading to death.   |

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- |                                |   |
|--------------------------------|---|
| Suitable extinguishing media   | : Alcohol resistant foam. Dry powder. Carbon dioxide (CO2) to. Water spray. Sand. |
| Unsuitable extinguishing media | : Do not use a solid water stream as it may scatter and spread fire.              |

### 5.2. Special hazards arising from the substance or mixture

- |                  |   |
|------------------|---|
| Fire hazard      | : Combustible liquid.   |
| Explosion hazard | : May form flammable/explosive vapor-air mixture. Vapor heavier than air may travel considerable distance to a source of ignition and flash back. |

### 5.3. Advice for firefighters

- |                                       |   |
|---------------------------------------|---|
| Firefighting instructions             | : Prevent runoff from entering drains, sewers or waterways. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.   |
| Protective equipment for firefighters | : Do not enter fire area without proper protective equipment, including respiratory protection. Wear a self contained breathing apparatus.  |
| Other information                     | : Combustible liquid. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Use water spray to cool unopened containers. Alcohols burn with a pale blue flame which may be extremely hard to see under normal lighting conditions. Personnel may be able to feel the heat of the fire without seeing flames. Extreme caution must be exercised in fighting alcohol fires. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors. Move undamaged containers from immediate hazard area if it can be done safely. On burning: release of carbon monoxide - carbon dioxide. unburned hydrocarbons. Formaldehyde. |

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- |                  |  |
|------------------|--|
| General measures | : Stop leak if safe to do so. Avoid breathing dust, fume, mist, spray, vapors. Avoid contact with skin, eyes and clothing. Eliminate all ignition sources if safe to do so. No open flames. No smoking. Use special care to avoid static electric charges. |
|------------------|--|

#### 6.1.1. For non-emergency personnel

- |                      |   |
|----------------------|---|
| Protective equipment | : Wear suitable protective clothing. For further information refer to section 8: "Exposure controls/personal protection". |
| Emergency procedures | : Evacuate unnecessary personnel.   |

#### 6.1.2. For emergency responders

- |                      |   |
|----------------------|---|
| Protective equipment | : Avoid breathing dust, fume, mist, spray, vapors. Equip cleanup crew with proper protection. |
| Emergency procedures | : Ventilate area.   |

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

# JAUNDEXTONE

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### 6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Keep upwind of the spilled material and isolate exposure . Wear proper protective equipment. Contain large spillage with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Gather the product and place it in a spare container that has been suitably labelled. Store away from other materials. Small spills may be flushed to a sanitary sewer with copious amounts of water, if in accordance with local, state or national legislation. Eliminate all sources of ignition, avoid sparks, flames and do not smoke in risk area. Ensure all national and local regulations are observed. Incinerate, dispose in sanitary landfill - if permitted. Consult the appropriate authorities about waste disposal.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Work in a well-ventilated area. Avoid breathing dust, fume, mist, spray, vapors. Keep away from clothing as well as other incompatible materials. Avoid contact with skin, eyes and clothing. Provide good ventilation in process area to prevent formation of vapor. Keep away from heat, sparks, open flames, hot surfaces. - No smoking. Take precautionary measures against static discharge.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practices. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : A washing facility for eye and skin cleaning purposes should be present. Ensure adequate ventilation. Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.
- Storage conditions : Protect containers against physical damage. Keep only in the original container in a cool, well ventilated place. Store away from direct sunlight or other heat sources. Keep container tightly closed.
- Incompatible materials : Strong acids, bases. Oxidizing agents.
- Heat and ignition sources : Store away from direct sunlight or other heat sources.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

<b>Methyl alcohol (67-56-1)</b>		
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm

  

<b>Formaldehyde (50-00-0)</b>		
USA ACGIH	ACGIH Ceiling (ppm)	0.3 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	0.75 ppm
USA OSHA	OSHA PEL (STEL) (ppm)	2 ppm (see 29 CFR 1910.1048)

  

<b>Boric acid, disodium salt, pentahydrate (12179-04-3)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (inhalable fraction)
USA ACGIH	ACGIH STEL (mg/m <sup>3</sup> )	6 mg/m <sup>3</sup> (inhalable fraction)

  

<b>Boric acid (H3BO3) (10043-35-3)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (inhalable fraction)
USA ACGIH	ACGIH STEL (mg/m <sup>3</sup> )	6 mg/m <sup>3</sup> (inhalable fraction)

# JAUNDEXTONE

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### 8.2. Exposure controls

Appropriate engineering controls	: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide adequate ventilation. Monitoring the effectiveness of engineering control is recommended.
Personal protective equipment	: Avoid all unnecessary exposure. Wear protective clothing, protective gloves, eye protection/goggles, face protection. For certain operations, additional Personal Protection Equipment (PPE) may be required.
Hand protection	: Wear impermeable protective nitrile gloves. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.
Eye protection	: Contact lenses should not be worn. Chemical goggles and face shields are required to prevent potential eye contact, irritation or injury.
Skin and body protection	: Long sleeved protective clothing. Overall. Rubber apron, boots. safety foot-wear.
Respiratory protection	: In case of insufficient ventilation. Wear suitable respiratory equipment. Approved organic vapor respirator.
Environmental exposure controls	: Avoid discharge to the environment.
Other information	: Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear
Color	: Red
Odor	: Pungent odor
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: 1
Melting point	: No data available
Freezing point	: -1 °C ( 30 °F )
Boiling point	: 96 °C ( 205 °F )
Flash point	: 90 °C ( 194°F COC )
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: 1
Relative density	: No data available
Density	: 1.026 Specific Gravity
Solubility	: Water: completely soluble
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 7 - 73 vol %

### 9.2. Other information

VOC content	: 6 % (Percent volatiles)
-------------	---------------------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Stable under normal conditions. Unstable on exposure to heat. Combustible liquid. May form flammable/explosive vapor-air mixture.

# JAUNDEXTONE

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. heat, sparks, open flames, hot surfaces. heat sources.

### 10.5. Incompatible materials

Oxidizing agents. Strong acids. strong bases.

### 10.6. Hazardous decomposition products

Thermal decomposition generates : Corrosive vapors. Fume. Carbon monoxide. Carbon dioxide. Formaldehyde.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Harmful if swallowed. Harmful in contact with skin.

<b>Methyl alcohol (67-56-1)</b>	
LC50 inhalation rat (ppm)	22500 ppm (Exposure time: 8 h)
ATE US (oral)	100.00000000 mg/kg bodyweight
ATE US (dermal)	300.00000000 mg/kg bodyweight
ATE US (vapors)	3.00000000 mg/l/4h

<b>Formaldehyde (50-00-0)</b>	
LD50 oral rat	600 mg/kg
LD50 dermal rabbit	270 mg/kg
LC50 inhalation rat (mg/l)	0.578 mg/l/4h
ATE US (oral)	100.00000000 mg/kg bodyweight
ATE US (dermal)	270.00000000 mg/kg bodyweight
ATE US (gases)	700.00000000 ppmv/4h
ATE US (vapors)	0.57800000 mg/l/4h
ATE US (dust,mist)	0.57800000 mg/l/4h

<b>Boric acid, disodium salt, pentahydrate (12179-04-3)</b>	
LD50 oral rat	2403 mg/kg
ATE US (oral)	2403.00000000 mg/kg bodyweight

<b>Boric acid (H3BO3) (10043-35-3)</b>	
LD50 oral rat	2660 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 0.16 mg/l/4h
ATE US (oral)	2660.00000000 mg/kg bodyweight

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitisation : May cause an allergic skin reaction.  
Germ cell mutagenicity : Not classified  
(Based on available data, the classification criteria are not met)  
Carcinogenicity : May cause cancer.

<b>Formaldehyde (50-00-0)</b>	
IARC group	1 - Carcinogenic to humans
National Toxicity Program (NTP) Status	2 - Known Human Carcinogens

Reproductive toxicity : Not classified  
(Based on available data, the classification criteria are not met)

Specific target organ toxicity (single exposure) : May cause damage to organs.

Specific target organ toxicity (repeated exposure) : Not classified  
(Based on available data, the classification criteria are not met)

# JAUNDEXTONE

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
Potential Adverse human health effects and symptoms	: Harmful if inhaled. Toxic if swallowed. Toxic in contact with skin.
Symptoms/injuries after inhalation	: Harmful if inhaled. May cause respiratory irritation. Danger of serious damage to health by prolonged exposure through inhalation. May cause cancer by inhalation. Difficulty in breathing. Causes damage to liver through prolonged or repeated exposure if inhaled. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination. Death in extreme cases.
Symptoms/injuries after skin contact	: Harmful in contact with skin. May cause an allergic skin reaction. Causes skin irritation. Absorbed through the skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard. Contains formaldehyde which can combine with epidermal protein to produce a hapten-protein couple capable of sensitising T-lymphocytes. Subsequent exposures cause a type IV hypersensitivity reaction.
Symptoms/injuries after eye contact	: Causes serious eye irritation. Redness and pain. Impaired vision, watering of eyes, defects in the cornea. Burning sensation. Inflammation. Can cause blindness.
Symptoms/injuries after ingestion	: Harmful if swallowed. Swallowing a small quantity of this material will result in serious health hazard. This material contains methanol, which, when ingested, has caused acidosis, ocular toxicity ranging from diminished visual capacity to complete blindness, and death. Ingestion may cause nausea, vomiting and diarrhea. Swallowing can cause severe injury leading to death.

## SECTION 12: Ecological information

### 12.1. Toxicity

Formaldehyde (50-00-0)	
LC50 fishes 1	22.6 - 25.7 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	2 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	1510 µg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 2	11.3 - 18 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

  

Boric acid (H3BO3) (10043-35-3)	
EC50 Daphnia 1	115 - 153 mg/l (Exposure time: 48 h - Species: Daphnia magna)

### 12.2. Persistence and degradability

JAUNDEXTONE	
Persistence and degradability	Not established.

### 12.3. Bioaccumulative potential

JAUNDEXTONE	
Bioaccumulative potential	Not established.

  

Formaldehyde (50-00-0)	
Log Pow	0.35 (at 25 °C)

  

Boric acid (H3BO3) (10043-35-3)	
BCF fish 1	0
Log Pow	-0.757 (at 25 °C)

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on ozone layer	: No additional information available
Effect on the global warming	: No known ecological damage caused by this product.
Other information	: Avoid release to the environment.



# JAUNDEXTONE

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

- Waste disposal recommendations : It is the responsibility of the user to determine if disposal material is hazardous according to federal, state and local regulations. Dispose of contents and container to comply with applicable local, national and international regulations. Consult the appropriate authorities about waste disposal. Do not pressurize, cut, weld, braze solder, drill, grind, or expose containers to flames, sparks, heat, or other potential ignition sources. Do not re-use empty containers. Dispose in a safe manner in accordance with local and national regulations.
- Incinerate, dispose in sanitary landfill - if permitted. Ensure all national and local regulations are observed.
- Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

### SECTION 14: Transport information

In accordance with DOT  
Not regulated for transport

#### Additional information

Other information : No supplementary information available.

#### Transport by sea

Not regulated for transport

#### Air transport

Not regulated for transport

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

JAUNDEXTONE	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	1250 lb
Methyl alcohol (67-56-1)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	5000 lb
SARA Section 313 - Emission Reporting	1.0 %
Formaldehyde (50-00-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on the United States SARA Section 302 Listed on United States SARA Section 313	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	100 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	500
SARA Section 313 - Emission Reporting	0.1 %

#### 15.2. International regulations

##### CANADA

Formaldehyde (50-00-0)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Boric acid (H3BO3) (10043-35-3)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

##### EU-Regulations

Formaldehyde (50-00-0)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	

# JAUNDEXTONE

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

No additional information available

### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

No additional information available

### 15.2.2. National regulations

#### Formaldehyde (50-00-0)

Listed on IARC (International Agency for Research on Cancer)  
Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Japanese ISHL (Industrial Safety and Health Law)  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Japanese Poisonous and Deleterious Substances Control Law  
Japanese Pollutant Release and Transfer Register Law (PRTR Law)  
Listed as carcinogen on NTP (National Toxicology Program)  
Listed on the Canadian IDL (Ingredient Disclosure List)

### 15.3. US State regulations

#### Methyl alcohol (67-56-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
	Yes			

#### Formaldehyde (50-00-0)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes				

## SECTION 16: Other information

Other information : None.

Full text of H-phrases: see section 16:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Acute Tox. 3 (Inhalation:vapor)	Acute toxicity (inhalation:vapor) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Carc. 1A	Carcinogenicity, Category 1A
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 4	Flammable liquids Category 4
Repr. 1B	Reproductive toxicity Category 1B
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 2	Specific target organ toxicity (single exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H227	Combustible liquid

# JAUNDEXTONE

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H335	May cause respiratory irritation
H350	May cause cancer
H360	May damage fertility or the unborn child
H370	Causes damage to organs
H371	May cause damage to organs

### HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur  
Flammability : 2 Moderate Hazard  
Physical : 0 Minimal Hazard

SDS US (GHS HazCom 2012)

*The information herein given is in good faith but no warranty, expressed or implied, is made, except that to the best of the Company's knowledge it is accurate. The Champion Company does not assume any legal responsibilities for use or dependence upon same. Customers may wish to conduct tests of their own. The user is urged to read the information provided on the label before using product.*