



**PK  
CPF=20<sup>A</sup>**

**Glutaraldehyde/Lanolin Based Arterial Fluid with Entrone and AD-P**

PK is a glutaraldehyde arterial fluid which contains Entrone for achieving penetration to the point of complete saturation and AD-P for control of aldehyde action to obtain better diffusion and improvement of cosmetic effect. In addition, PK contains ultra-fine lanolins and cosmetic oils to prevent dehydration and produce a natural look and texture to tissues. PK has a superior sanitizing action due to the glutaraldehyde present. PK is suitable for use in all normal embalming situations. PK is not recommended in cases of edema or advanced decomposition.

PH-A <sup>1</sup>	PK <sup>B</sup>		TRI-SAN <sup>3</sup> ADD FOR EXTRA FIRMNESS	ALOE FACTOR <sup>4</sup> ADD TO RESTORE MOISTURE CONTENT
	MODERATE FIRMNESS	DEFINITE <sup>2</sup> FIRMNESS		
<b>3-4</b>	<b>8-10</b>	<b>12-14</b>	<b>2-4</b>	<b>4-8</b>
→ → <b>MIX IN THIS ORDER</b> → → <b>OUNCES PER GALLON</b>				

**Notes:**

- A - A value assigned to all Champion fluids ranking them on the basis of preservative ability using recommended dilutions in normal cases. The Champion Preservative Factor is not index but can equal it in certain fluids. It is derived from the total chemical composition of each fluid and results of extensive field research. The Champion Preservative Factor can be used by the embalmer to predict the reactivity, preservative value and firming action of Champion fluids.
- B - Add Champion Coloro Dyes as needed to achieve desired cosmetic effect.
- 1 - For proper water conditioning and pH balance to maximize fluid efficiency (if using soft water - reduce amount to 2-3 ozs.)
- 2 - These are recommended amounts for normal cases. Additional amounts of fluid will be needed for cases with higher aldehyde demand such as cancer, renal and liver diseases with their complications, institutional cases and other wasting diseases, delayed embalming cases, edema and bodies subjected to extensive drug therapy.
- 3 - For increased aldehyde action of fluid with improved rigidity and preservation. (Increases preservative factor of fluid without inducing dehydration or other unwanted effects.)
- 4 - For maximum rehydration of tissues. Restores moisture in cases of dehydration or emaciation. Use in last I to 1-1/2 gallons of solution with intermittent or restricted drainage.

**BEFORE USING, READ SAFETY DATA SHEET.  
FOR PROFESSIONAL EMBALMING USE ONLY.**

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name : PK

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Arterial Embalming Fluid

Use of the substance/mixture : For professional use only

#### 1.3. Details of the supplier of the safety data sheet

THE CHAMPION COMPANY  
400 Harrison Street  
Springfield, Ohio 45505

Telephone No. (937) 324-5681

#### 1.4. Emergency telephone number

INFOTRAC: 1-800-535-5053 DOMESTIC or 352-323-3500 INTERNATIONAL

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Acute Tox. 4 (Oral)	H302
Acute Tox. 3 (Dermal)	H311
Acute Tox. 4 (Inhalation:dust,mist)	H332
Skin Irrit. 2	H315
Eye Dam. 1	H318
Resp. Sens. 1	H334
Skin Sens. 1	H317
Carc. 1A	H350
STOT SE 3	H335
STOT SE 1	H370

#### 2.2. Label elements

##### GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H302+H332 - Harmful if swallowed or if inhaled  
H311 - Toxic in contact with skin  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled  
H335 - May cause respiratory irritation  
H350 - May cause cancer  
H370 - Causes damage to organs

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P260 - Do not breathe dust, fume, mist, spray, vapors  
P261 - Avoid breathing dust, fume, mist, spray, vapors  
P264 - Wash hands thoroughly after handling  
P270 - Do not eat, drink or smoke when using this product  
P271 - Use only in a well-ventilated area  
P272 - Contaminated work clothing must not be allowed out of the workplace  
P280 - Wear protective clothing, protective gloves, eye protection, face protection  
P285 - In case of inadequate ventilation wear respiratory protection  
P301+P312 - If swallowed: Call a POISON CENTER  
P302+P352 - If on skin: Wash with plenty of water  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 P307+P311 - If exposed: Call a doctor  
 P308+P313 - If exposed or concerned: Get medical attention  
 P310 - Immediately call a POISON CENTER  
 P312 - Call a POISON CENTER  
 P330 - Rinse mouth  
 P332+P313 - If skin irritation occurs: Get medical attention  
 P333+P313 - If skin irritation or rash occurs: Get medical attention  
 P342+P311 - If experiencing respiratory symptoms: Call a doctor  
 P361 - Take off immediately all contaminated clothing  
 P362 - Take off contaminated clothing and wash before reuse  
 P363 - Wash contaminated clothing before reuse  
 P403+P233 - Store in a well-ventilated place. Keep container tightly closed  
 P405 - Store locked up  
 P501 - Dispose of contents and container to comply with applicable local, state, national and international regulation.

### 2.3. Other hazards

other hazards which do not result in classification : Spills of this product present a serious slipping hazard.

### 2.4. Unknown acute toxicity (GHS-US)

No data available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Methyl alcohol	(CAS No) 67-56-1	10 - 18	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapor), H331 STOT SE 1, H370
Formaldehyde	(CAS No) 50-00-0	≤ 13	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 1A, H350 STOT SE 3, H335
Glutaraldehyde	(CAS No) 111-30-8	≤ 6	Flam. Liq. 4, H227 Acute Tox. 3 (Oral), H301 Acute Tox. 2 (Inhalation:dust,mist), H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1, H317 STOT SE 3, H335
Boric acid, disodium salt, pentahydrate	(CAS No) 12179-04-3	2	Repr. 1B, H360
Ethyl formate	(CAS No) 109-94-4	< 0.3	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2A, H319 STOT SE 3, H335
Oils, cedarwood, Texan	(CAS No) 68990-83-0	< 0.3	Asp. Tox. 1, H304

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Give artificial respiration if necessary. Immediately get medical attention.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation occurs: Get medical attention.

# PK

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

- First-aid measures after eye contact : In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention immediately.
- First-aid measures after ingestion : If swallowed, rinse mouth with water (only if the person is conscious). Call a POISON CENTER. Obtain emergency medical attention. Give water or milk if the person is fully conscious. Never give anything by mouth to a person who is not fully conscious. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Causes damage to organs.
- Symptoms/injuries after inhalation : Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Inhalation of concentrated vapors may cause serious damage to the lining of the nose, throat, and lungs. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination. Difficulty in breathing. Danger of serious damage to health by prolonged exposure through inhalation. May cause cancer by inhalation. Causes damage to liver through prolonged or repeated exposure if inhaled.
- Symptoms/injuries after skin contact : Toxic in contact with skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard. May cause an allergic skin reaction. Causes skin irritation. Redness. Dermatitis.
- Symptoms/injuries after eye contact : Causes serious eye damage. Can cause blindness.
- Symptoms/injuries after ingestion : Harmful if swallowed. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Ingestion may cause nausea and vomiting. Can cause blindness. Death in extreme cases.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

### 5.2. Special hazards arising from the substance or mixture

- Explosion hazard : Heating will cause pressure rise with risk of bursting and subsequent explosion. May form flammable/explosive vapor-air mixture. Vapors can travel considerable distances to a source of ignition where they can ignite, flash back, or explode.

### 5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protective equipment for firefighters : Do not enter fire area without proper protective equipment, including respiratory protection. Wear a self contained breathing apparatus.
- Other information : Special danger of slipping by leaking and spilling product. Thermal combustion may release carbon monoxide and dioxide. unburned hydrocarbons. Toxic gases and fumes may be released in a fire.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid breathing dust, fume, mist, spray, vapors. Stop leak if safe to do so. Surface will become slippery when wet or damp. No naked lights. No smoking. Take precautionary measures against static discharge.

#### 6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

**6.3. Methods and material for containment and cleaning up**

- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Collect all waste in suitable and labelled containers and dispose according to local legislation. Ensure all national and local regulations are observed. Thoroughly wash the area with water after a spill or leak clean-up. Dispose of waste according to applicable legislation.

**6.4. Reference to other sections**

See Heading 8. Exposure controls and personal protection.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

- Precautions for safe handling : Obtain special instructions before use. Avoid contact with skin and eyes. Work in a well-ventilated area. When not in use, keep containers tightly closed. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
- Hygiene measures : Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practices.

**7.2. Conditions for safe storage, including any incompatibilities**

- Technical measures : Provide local exhaust or general room ventilation. A washing facility for eye and skin cleaning purposes should be present.
- Storage conditions : Keep out of reach of children. Keep only in the original container in a cool, well-ventilated place away from highly flammable substances. Keep container tightly closed and dry. Store away from direct sunlight or other heat sources.
- Incompatible materials : Strong acids, bases. Oxidizing agents.

**7.3. Specific end use(s)**

No additional information available

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters**

<b>Boric acid, disodium salt, pentahydrate (12179-04-3)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
USA ACGIH	ACGIH STEL (mg/m <sup>3</sup> )	6 mg/m <sup>3</sup>
<b>Glutaraldehyde (111-30-8)</b>		
USA ACGIH	ACGIH Ceiling (ppm)	0.05 ppm (activated and inactivated)
<b>Formaldehyde (50-00-0)</b>		
USA ACGIH	ACGIH Ceiling (ppm)	0.3 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	0.75 ppm
USA OSHA	OSHA PEL (STEL) (ppm)	2 ppm (see 29 CFR 1910.1048)
<b>Methyl alcohol (67-56-1)</b>		
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
<b>Ethyl formate (109-94-4)</b>		
USA ACGIH	ACGIH STEL (ppm)	100 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	300 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm

**8.2. Exposure controls**

- Appropriate engineering controls : Provide local exhaust or general room ventilation. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Personal protective equipment	: Avoid all unnecessary exposure. Wear protective clothing, protective gloves, eye protection/goggles, face protection. For certain operations, additional Personal Protection Equipment (PPE) may be required.
Hand protection	: Wear impermeable protective nitrile gloves. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.
Eye protection	: Contact lenses should not be worn. Chemical goggles and face shields are required to prevent potential eye contact, irritation or injury.
Skin and body protection	: Long sleeved protective clothing. Overall. Rubber apron, boots. safety foot-wear.
Respiratory protection	: In case of insufficient ventilation. Wear suitable respiratory equipment. Approved organic vapor respirator.
Other information	: Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Redish orange
Odor	: Mild pungent odor
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: 1
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 90.55 °C (195) °F
Flash point	: 93.33 °C (200 °F COC)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: ≈ 1
Relative density	: No data available
Density	: 1.04 Specific Gravity
Solubility	: Water: completely soluble
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 6.7 - 72 vol %

### 9.2. Other information

VOC content	: 18 % Percent Volatiles
-------------	--------------------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Stable at normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong acids. Strong bases. Oxidizing agents.

# PK

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### 10.6. Hazardous decomposition products

On thermal combustion form: Fume. Carbon monoxide. Carbon dioxide. unburned hydrocarbons. Toxic fumes.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Harmful if swallowed. Toxic in contact with skin. Harmful if inhaled.

<b>Boric acid, disodium salt, pentahydrate (12179-04-3)</b>	
LD50 oral rat	2403 mg/kg
ATE US (oral)	2403.00000000 mg/kg bodyweight

<b>Glutaraldehyde (111-30-8)</b>	
LD50 oral rat	252 mg/kg
LD50 dermal rabbit	560 µl/kg
LC50 inhalation rat (mg/l)	0.1 mg/l/4h
ATE US (oral)	252.00000000 mg/kg bodyweight
ATE US (vapors)	0.10000000 mg/l/4h
ATE US (dust,mist)	0.10000000 mg/l/4h

<b>Formaldehyde (50-00-0)</b>	
LD50 oral rat	500 mg/kg
LD50 dermal rabbit	270 mg/kg
LC50 inhalation rat (mg/l)	0.578 mg/l/4h
ATE US (oral)	100.00000000 mg/kg bodyweight
ATE US (dermal)	270.00000000 mg/kg bodyweight
ATE US (gases)	700.00000000 ppmv/4h
ATE US (vapors)	0.57800000 mg/l/4h
ATE US (dust,mist)	0.57800000 mg/l/4h

<b>Methyl alcohol (67-56-1)</b>	
LC50 inhalation rat (mg/l)	130.7 mg/l/4h (lit. ECHA)
ATE US (oral)	100.00000000 mg/kg bodyweight
ATE US (dermal)	300.00000000 mg/kg bodyweight
ATE US (vapors)	3.00000000 mg/l/4h

<b>Ethyl formate (109-94-4)</b>	
LD50 oral rat	1850 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
ATE US (oral)	1850.00000000 mg/kg bodyweight
ATE US (gases)	4500.00000000 ppmv/4h
ATE US (vapors)	11.00000000 mg/l/4h
ATE US (dust,mist)	1.50000000 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Causes serious eye damage.  
Respiratory or skin sensitisation : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.  
Germ cell mutagenicity : Not classified  
Carcinogenicity : May cause cancer.

<b>Formaldehyde (50-00-0)</b>	
IARC group	1 - Carcinogenic to humans
National Toxicity Program (NTP) Status	2 - Known Human Carcinogens

Reproductive toxicity : Not classified  
Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure) : May cause respiratory irritation. Causes damage to organs.

Specific target organ toxicity (repeated exposure) : Not classified  
Based on available data, the classification criteria are not met.

Aspiration hazard	: Not classified Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Inhalation of concentrated vapors may cause serious damage to the lining of the nose, throat, and lungs. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination. Difficulty in breathing. Danger of serious damage to health by prolonged exposure through inhalation. May cause cancer by inhalation. Causes damage to liver through prolonged or repeated exposure if inhaled.
Symptoms/injuries after skin contact	: Toxic in contact with skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard. May cause an allergic skin reaction. Causes skin irritation. Redness. Dermatitis.
Symptoms/injuries after eye contact	: Causes serious eye damage. Can cause blindness.
Symptoms/injuries after ingestion	: Harmful if swallowed. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Ingestion may cause nausea and vomiting. Can cause blindness. Death in extreme cases.

## SECTION 12: Ecological information

### 12.1. Toxicity

Glutaraldehyde (111-30-8)	
LC50 fishes 1	7.8 - 22 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	14 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	2.6 - 4.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 Daphnia 2	0.56 - 1.0 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
Formaldehyde (50-00-0)	
LC50 fishes 1	22.6 - 25.7 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	2 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	1510 µg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 2	11.3 - 18 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
Methyl alcohol (67-56-1)	
LC50 fishes 1	> 12700 mg/l 96 hours
EC50 Daphnia 1	> 10000 mg/l

### 12.2. Persistence and degradability

PK	
Persistence and degradability	Not established.

### 12.3. Bioaccumulative potential

PK	
Bioaccumulative potential	Not established.
Glutaraldehyde (111-30-8)	
Log Pow	0.22 (at 25 °C)
Formaldehyde (50-00-0)	
Log Pow	0.35 (at 25 °C)
Ethyl formate (109-94-4)	
BCF fish 1	(will not bioconcentrate)

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on ozone layer	: No additional information available
Effect on the global warming	: No additional information available
Other information	: Avoid release to the environment.



# PK

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### SECTION 13: Disposal considerations


#### 13.1. Waste treatment methods

- Waste disposal recommendations : Dispose in a safe manner in accordance with local and national regulations. Incinerate, dispose in sanitary landfill - if permitted. Ensure all national and local regulations are observed.
- Additional information : Do not re-use empty containers. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose containers to flames, sparks, heat, or other potential ignition sources.
- Ecology - waste materials : Avoid release to the environment.

### SECTION 14: Transport information

In accordance with DOT

- Transport document description : UN2922, Corrosive liquids, toxic, n.o.s. (Formaldehyde, Methanol), 8, PGIII, ltd.qty.
- Hazard labels (DOT) : 8 - Corrosive  
6.1 - Poison inhalation hazard



- Packing group (DOT) : III - Minor Danger
- DOT Packaging Exceptions (49 CFR 173.xxx) : 154
- DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
- DOT Packaging Bulk (49 CFR 173.xxx) : 241
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
- DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
- DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

#### Additional information

- Other information : No supplementary information available.

#### Transport by sea

No additional information available

#### Air transport

No additional information available

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

PK	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	769 lb
Formaldehyde (50-00-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on the United States SARA Section 302	
Listed on United States SARA Section 313	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	100 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	500
SARA Section 313 - Emission Reporting	0.1 %
Methyl alcohol (67-56-1)	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	5000 lb
SARA Section 313 - Emission Reporting	1.0 %

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

## 15.2. International regulations

## CANADA

Glutaraldehyde (111-30-8)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects Class E - Corrosive Material
Formaldehyde (50-00-0)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Ethyl formate (109-94-4)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects

## EU-Regulations

Formaldehyde (50-00-0)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	

## Classification according to Regulation (EC) No. 1272/2008 [CLP]

No additional information available

## Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

No additional information available

## 15.2.2. National regulations

Formaldehyde (50-00-0)	
Listed on IARC (International Agency for Research on Cancer)	
Listed on the AICS (Australian Inventory of Chemical Substances)	
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)	
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory	
Listed on the Japanese ISHL (Industrial Safety and Health Law)	
Listed on the Korean ECL (Existing Chemicals List)	
Listed on NZIoC (New Zealand Inventory of Chemicals)	
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)	
Japanese Poisonous and Deleterious Substances Control Law	
Japanese Pollutant Release and Transfer Register Law (PRTR Law)	
Listed as carcinogen on NTP (National Toxicology Program)	
Listed on the Canadian IDL (Ingredient Disclosure List)	

## 15.3. US State regulations

No additional information available

Formaldehyde (50-00-0)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes				
Methyl alcohol (67-56-1)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
	Yes			

**SECTION 16: Other information**

Other information : None.

Full text of H-phrases: see section 16:

Acute Tox. 2 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Acute Tox. 3 (Inhalation:vapor)	Acute toxicity (inhalation:vapor) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1A	Carcinogenicity, Category 1A
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 4	Flammable liquids Category 4
Repr. 1B	Reproductive toxicity Category 1B
Resp. Sens. 1	Sensitisation — Respiratory, category 1
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H227	Combustible liquid
H301	Toxic if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H330	Fatal if inhaled
H331	Toxic if inhaled
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H350	May cause cancer
H360	May damage fertility or the unborn child
H370	Causes damage to organs

**HMIS III Rating**

Health : 2 Moderate Hazard - Temporary or minor injury may occur  
 Flammability : 2 Moderate Hazard  
 Physical : 0 Minimal Hazard

SDS US (GHS HazCom 2012)

*The information herein given is in good faith but no warranty, expressed or implied, is made, except that to the best of the Company's knowledge it is accurate. The Champion Company does not assume any legal responsibilities for use or dependence upon same. Customers may wish to conduct tests of their own. The user is urged to read the information provided on the label before using product.*